BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1302140S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1302140S lodged with the consent authority or certifier on 04 May 2022 with application 24/08/2022.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000

Secretary

Date of issue: Friday, 11 November 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	68 Grinton - Unit 2_	02		
Street address	68 Grinton Avenue	Ashmont 2650		
Local Government Area	Wagga Wagga City	Council		
Plan type and plan number	deposited 1093875			
Lot no.	12			
Section no.	-			
Project type	separate dwelling he	separate dwelling house		
No. of bedrooms	3	3		
Project score				
Water	26	Target 20		
Thermal Comfort	V Pass	Target Pass		
Energy	v 41	Target 40		

Certificate Prepared by

Name / Company Name: Chris Kendall

ABN (if applicable): N/A

BASIX Planning, Industry & Environment www.basix.nsw.gov.au

Description of project

Project address

68 Grinton - Unit 2_02
68 Grinton Avenue Ashmont 2650
Wagga Wagga City Council
Deposited Plan 1093875
12
-
separate dwelling house
3
333
155
90.0
12.0
156

Assessor details and thermal lo	ads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m ² .year)	n/a	
Area adjusted heating load (MJ/m ² .year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	26	Target 20
Thermal Comfort	V Pass	Target Pass
Energy	V 41	Target 40

BASIX

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 156 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		~	

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	2.20 (or 2.60 including construction)	
internal wall shared with garage - plasterboard	0.84 (or 1.20 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 2.75 (up), roof: foil/sarking	unventilated; light (solar absorptance < 0.475)

Note
 Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
 Note
 In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

 BASIX
 Planning, Industry & Environment
 www.basix.nsw.gov.au
 Version: 3.0 / DARWINIA_3_20_0
 Certificate No.: 1302140S_02
 Friday, 11 November 2022

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check		
Windows, glazed doors and skylights					
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	 	~		
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	 Image: A set of the set of the	~		
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~		
• For the following glass and frame types, the certifier check can be performed by visual inspection.			v		
- Aluminium single clear					
- Aluminium double (air) clear					
- Timber/uPVC/fibreglass single clear					
- Timber/uPVC/fibreglass double (air) clear					

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W01	1200	1500	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
W02	900	600	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
W03	1200	1800	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
East facing					
W05	1800	750	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
W04	900	600	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
W06	1800	1800	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed

BASIX Planning, Industry & Environment www.basix.nsw.gov.au

asix.nsw.gov.au Version: 3.0

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
South facing					
W07	2100	2100	aluminium, single, clear	eave 3200 mm, 170 mm above head of window or glazed door	not overshadowed
W08	1200	1500	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
West facing	1				
W09	1500	1800	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed
W10	600	1800	aluminium, single, clear	eave 600 mm, 170 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	v	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase irconditioning; Energy rating: EER 3.0 - 3.5		~	~
he applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase irconditioning; Energy rating: EER 3.0 - 3.5		~	~
leating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase irconditioning; Energy rating: EER 3.0 - 3.5		 ✓ 	~
he applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase irconditioning; Energy rating: EER 3.0 - 3.5		~	~
/entilation			
he applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		_	v
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		 Image: A set of the set of the	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the ollowing rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent of ght emitting diode (LED) lamps:	e Sr		
 at least 3 of the bedrooms / study; 		_	
at least 2 of the living / dining rooms;			
• the kitchen;			

Certificate No.: 1302140S_02

Friday, 11 November 2022

BASIX

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets;		~	~
the laundry;		~	~
• all hallways;		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		_	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.